

GT5000

“Presenting” the GT5000 Series TTW ATM

Genmega introduces the GT5000 series ATM. A high performance yet economical Through-The-Wall ATM solution with the look and feel of a full bank ATM. Designed for wall or Kiosk installation, the GT5000 series makes new TTW installation or replacements a snap. Built with the same compact modular components as your existing Genmega machines and engineered for easy installation and reliable operation. The GT5000 includes high-end features like a 15" High Bright LCD which support custom advertisements and a 3-cassette cash dispenser with motorized cash presenter. A new Touch-Screen rear-service panel allows convenient and safe access for ATM Operators and Service personal.

The GT5000 series ATM is ADA compliant and Chip Card (EMV) ready, including a PCI / Interac certified encrypting PIN pad (EPP), a voice guidance system, and lighted action indicators (including lighted keypad). Features of a high end Through-The-Wall ATM with the low maintenance and reliability that Genmega delivers makes this an excellent TTW solution.



GENMEGA

GT5000

Integrated Illuminated Topper Sign

High Visibility LED Sign
Attract Customers

LCD Screen

15 inch color TFT-LCD Panel
High bright LED backlight (800cd/m²)
1024 x 768 (XGA) Resolution

Printer

80mm/3" Receipt Printer
200DPI monographic printing

PIN Entry Device

16-key alphanumeric keypad
PCI 3.0 / Interac Certified
Triple-DES (TDES) compliant EPP

Rear Service Panel

7 inch color touch screen
Backlit TFT LCD panel
800 x 480 Resolution

Communication

56Kb Internal Modem
TCP/IP Ethernet - SSL



CPU

Cortex-A8 CPU (800MHz)
DDR2 256MB SRAM memory
512MB Flash Memory
Windows CE 6.0

ADA

Voice Guidance
Lighted Transaction Guidance
Accessible Keypad Layout

Card Reader

DIP Style Magnetic Card Reader
EMV - Optional

Security

UL291 Business Hours Vault
Electronic Lock or Cencon (optional)

Cash Dispenser

Up to 3 x 1700 Note Removable Cassette
Up to 3 x 2000 Note Removable Cassette
Presenter module

Dimensions

Height = 56.7"
Width = 24.1"
Depth = 33.9"
Weight = 570 lbs

Operating Environment

Temperature range : 40°F - 95°F
Relative humidity : Non-condensing=15%-85%

Power Requirements

110/220 VAC ± 10%, 50/60 Hz, 145 Watts



www.genmega.com